



## DATA AND SPECIFICATIONS

### 1. PRODUCT NAME

PROFLEX® Vinyl Expansion Joint

### 2. MANUFACTURER

Oscoda Plastics®, Inc.

P.O. Box 189

5585 N. Huron Avenue

Oscoda, MI 48750

Phone: 800-544-9538

989-739-6900

FAX: 800-548-7678

989-739-1494

www.oscodaplastics.com

E-Mail: sales@oscodaplastics.com

### 3. PRODUCT DESCRIPTION

PROFLEX Vinyl Expansion Joints are manufactured from 100% recycled vinyl with fabric strand reinforcement, obtained from the automotive and roofing industries. PROFLEX is easy to handle, will not rot or become brittle when exposed to the weather, and is extremely durable and flexible. Because of its flexibility, it will not break, split or crack when exposed to the elements. PROFLEX does not use adhesive binders in the manufacturing process, and can be stored outside.

### 4. APPLICATION

PROFLEX is ideal for any concrete application requiring an expansion joint filler or isolation joint, such as; sidewalks, driveways, parking lots, swimming pools, curbs, gutters, and a sill plate in residential homes, garages, and industrial buildings. Due to its flexibility, PROFLEX can be used for radius filler and concrete forms.

### 5. SPECIFICATIONS (Standard Sizes)

Thickness: ¼"

Width 5' Length: 3", 3½", and 4"

Thickness: ½"

Width 5' Length: 3½", 4", 6", and 36"

Width 10' length: 3 ½", 4"

Thermal Resistance: ¼" (avg.) .326

½" (avg.) .712

### 6. PACKAGING

Ten strips per bundle\*

Contact Oscoda Plastics or your local distributor for ordering requirements and sizes not listed.

- Special order sizes require a two pallet minimum purchase.

\*Ten foot lengths are packaged *five* strips per bundle.

